

SURFACE-EMITTING LASER DEVICES WITH
INTEGRATED BEAM-SHAPING OPTICS AND
POWER-MONITORING DETECTORS

5 This application claims the benefit of United States provisional patent application No. 60/208,289, filed on May 31, 2000, and United States provisional patent application No. 60/219,701, filed on July 18, 2000, both of which are hereby incorporated by reference herein in their entireties.

10 Background of the Invention

This invention relates to the field of semiconductor lasers, and more particularly to surface-emitting semiconductor lasers useful in optical fiber communication systems.

15 Semiconductor Edge Emitting Lasers (EELs) have been historically used as light sources in optical fiber communication systems. To meet a universally increasing demand for data transmission links and telecommunications there is a commercial need to fully
20 exploit the capabilities of optical fiber communication systems. The amount of data and distance over which signals can be transmitted over optical fibers is related to the wavelength of the carrier light beam. For example, the standard carrier light wavelengths for
25 optical fiber communication systems, as a function of the reach of the systems, are progressively higher into

09074229-052404
FOF29-052404

the near infrared radiation band. The standard carrier wavelengths are, for example, about 820 nm for short haul applications, about 1.31 μm for intermediate haul applications, and about 1.55 μm for long haul applications. The increasing demand for faster and cheaper data transmission links and telecommunications has highlighted deficiencies of EELs used at light sources at these near infrared wavelengths. These deficiencies include, for example, high manufacturing costs, and less than optimal beam cross-section for coupling to optical fibers.

EEL devices are generally mass produced using semiconductor wafers. Several horizontal dielectric waveguides may be diffused into or epitaxially grown on the surface of a wafer. The wafer is cleaved to section the dielectric waveguides into lasing cavities. Cleaved wafer facets at the ends of the waveguide sections serve as laser cavity mirrors. Even though EEL manufacturing processes seem straight forward, conventionally manufactured EEL devices must undergo heavy screening or testing for reliability. The structure of EEL devices does not lend itself to on-wafer testing of individual laser devices. Typically, the wafer is diced to separate individual laser devices. Each individual laser device is then mounted on a carrier and tested before being packaged for sale. This unavoidable individual testing of EEL devices contributes significantly to manufacturing costs.

Further, light emission in EEL devices is parallel to the wafer surface and out from the side through cleaved ends of the laser cavities. The emitted light beams are divergent, and have elliptical

cross-sections. The elliptical cross-sections are not suitable for efficient coupling of the light beams to optical fibers. Additional external focusing or beam-shaping optics must be used to couple the light beams to optical fibers. For wavelengths in the near infrared band such as 1.3 μm and 1.55 μm the focusing optics can be expensive, technologically complex and difficult.

In addition to these deficiencies, EELs generally have poor lasing mode stability. Traditionally, separate back facet power-monitoring detectors are used to monitor laser output and to provide feedback to laser drive circuitry for stabilizing laser output. Even with feedback control laser stability is poor at near infrared wavelengths.

Another type of laser, the so-called vertical cavity surface-emitting laser (VCSEL), has properties which are more desirable than those of EELs for optical fiber communication systems. VCSELs also are made from semiconductor wafers. Several vertical laser cavities perpendicular to the wafer surface are epitaxially grown on the wafer. Light emission is perpendicular to the surface of the wafers. The light beams emitted by the vertical cavities have circular cross-sections. Light beams with circular cross-sections are relatively easy to couple to optical fibers. External beam-shaping optics may not be necessary. Moreover, the structure of the VCSELs and their manufacturing processes lend themselves to on-wafer testing of individual laser devices. Unlike EEL devices, VCSEL devices do not have to be diced and individually mounted for testing. On-wafer testing leads to

09071229-053404
40250-6227250

manufacturing cost savings. Further, the VCSELs operating at 850 nm have good spectral characteristics.

FIG. 1 illustrates the structure of a typical VCSEL device operating at about 850 nm wavelength.

5 VCSEL 1 is epitaxially grown on a gallium arsenide (GaAs) substrate 13 and includes a top distributed Bragg reflector (DBR) 10, a quantum-well active region 11, a bottom DBR 12. Both DBR 10 and 12 are made of alternating layers of GaAs and aluminum gallium
10 arsenide (AlGaAs). The two DBRs act as mirrors and define a vertical lasing cavity in between themselves. VCSEL 1 produces output light beam 14 perpendicular to the wafer surface through top DBR 10. A small fraction of output light beam 14 may be diverted and monitored
15 by a separate photodetector for feedback control (not shown).

Recent advances in compound semiconductor (e.g., GaAs/AlGaAs) epitaxial growth technology and refinements of other manufacturing processes have
20 enabled low-cost mass production of VSCELs operating at about 850 nm. These low-cost VSCELs with their superior performance have almost completely supplanted the use of EELs, for example, in short haul communication applications that use the nominal 850 nm
25 carrier wavelength.

However, VCSELs devices do not operate well at the higher wavelengths of 1.3 μm and 1.55 μm that are suitable, for example, for intermediate and long haul applications, respectively. High optical cavity
30 losses, and high non-radiative recombination rates combined with decreased efficiency of GaAs/AlGaAs DBR mirrors at these higher wavelengths result in poor VCSEL performance.

2025 RELEASE UNDER E.O. 14176

Some other surface-emitting laser (SEL) structures that have horizontal lasing cavities are of current research interest. These SEL structures incorporate integrated on-wafer reflective structures in an attempt to mitigate the need for external beam-shaping optics. The reflective structures in these SELs are used to redirect horizontally propagating light radiation to a vertical direction. These SEL structures may be broadly categorized as either grating-coupled or beam-deflecting mirror types of SELs, depending on the type of reflective structure used.

The reflective structures in the grating-coupled SELs are gratings etched into the wafer surface above the horizontal lasing cavities. FIG. 2 illustrates the structure of a typical grating-coupled laser. Laser 2 consists of grating 20 disposed on top of lasing cavity 21. Metal electrode contacts 22 and 23 disposed on the top and bottom surfaces of laser 2, respectively, are connected to laser driver circuits (not shown). Second-order diffraction effects couple in-plane light radiation propagating in laser cavity 21 to produce output beam 24 perpendicular to the wafer surface.

The reflective structures in beam-deflecting mirror type SELs are typically 45-degree etched mirrors. FIGS. 3 and 4 show the structures of lasers 3 and 4, respectively. Both lasers have 45-degree etched mirrors for beam deflection. In laser 3, etched mirror 31 is part of lasing cavity 33. Mirror 31 deflects in-plane light upward by 90 degrees toward dielectric mirror 30. Dielectric mirror 30 transmits a portion of the deflected light as output beam 34, and reflects

05871229 052104
TOP SECRET 62212850

another portion back to lasing cavity 33. In laser 4, etched mirror 41 is external to lasing cavity 42. One end of lasing cavity 42 is a 90-degree etched surface 40. Mirror 41 deflects the light beam exiting
5 etched surface 40 upward by 90 degrees to form output beam 44.

Both the typical grating-coupled and the beam-deflecting mirror types of SELs exhibit unsatisfactory laser performance. The laser
10 performance is poor at least in part because the reflecting structures often intrude on the lasing action of the laser cavity. In grating-coupled SELs poor laser performance results, for example, from increased scattering loss and non-uniform current
15 injection into the light-coupling region underneath the grating. Beam-deflecting mirror type SELs which have an angled mirror as part of the lasing cavity (e.g., laser 3 FIG. 3) tend to have large optical cavity losses. The large cavity losses result in undesirable
20 high laser threshold current and low output power.

Laser performance may be poor even when the 45-degree mirror is external to the laser cavity which has perpendicular edges (e.g., laser 4, FIG. 4). The 45-degree mirror does not improve the divergence or the
25 elliptical cross-section of the emitted light beam. Therefore, having a 45-degree mirror in the laser structure does not improve the efficiency of coupling light to an optical fiber. External beam-correction and focusing optics may still have to be used to couple
30 output light beams to an optical fiber.

Additionally, the etched reflective structures of these SEL types present severe challenges in manufacturing. Precise and reproducible etching of

09071229 "053404
09071229 "053404

45-degree mirrors in close proximity to perpendicular cavity ends is difficult, for example, because the 45-degree plane is not a naturally terminating etch plane in most semiconductors.

5 It is therefore desirable to have new surface-emitting laser device structures that have good operating characteristics at near infra-red wavelengths, are amenable to on-wafer testing, and provide efficient beam coupling to optical fibers.

10 Summary of the Invention

 In accordance with the present invention, surface-emitting laser devices with integrated beam-shaping optics are provided. The beam-shaping optics use the optical phenomenon of total internal
15 reflection, transparent substrates, and refractive or diffractive micro-optic lenses to generate surface-emitted light output beams.

 The inventive laser device structure includes a lasing section and a beam-deflecting section. The
20 two sections are maintained in close physical and optical proximity for efficient transmission of laser radiation from the first section to the later section.

 The lasing section contains a horizontal lasing cavity, which can be similar to those in
25 conventional edge-emitting laser diodes. The lasing cavity is generally parallel to the top surface of the device. Cleaved or etched facets form the mirror ends of the lasing cavity. Light beams emitted by the lasing cavity exit one end of the lasing section and
30 propagate horizontally into the adjoining beam-deflection section of the device.

The beam-deflection section is made of a substrate which is transparent to the emitted light beams. A reflective mirror is formed on the bottom surface of the beam-deflection section. The

5 beam-deflecting section includes another mirror or deflecting surface in the path of the horizontally propagating light beams transmitted by the lasing section. This deflecting surface may be formed by a crystallographically terminating etch plane of the
10 substrate crystal. The deflecting surface is designed to make an angle with the horizontal which is greater than the critical angle for total internal reflection. The horizontally propagating light beams (from the lasing section) incident on the deflecting surface
15 undergo total internal reflection and are redirected downward toward the bottom surface. The reflective mirror at the bottom surface reflects downward incident light beams upwards toward the top surface of the laser device.

20 The beam-deflection section includes a micro-optic lens disposed on its top surface. This lens may be a refractive lens, a diffraction lens, or a combination. The lens may be designed to collimate (i.e., reduce the divergence) of upwardly redirected
25 light beams emerging through the top surface. The lens design may also be tailored so that the lens output beam has a more circular cross-section suitable for efficient coupling to optical fibers.

30 Optionally, a photodetector for monitoring the laser device output power may be integrated into the device structure. The photodetector may, for example, be a photodiode formed by depositing a metal

09071229-053404

electrode on a portion of the beam-deflecting section of the laser device.

The inventive laser devices may be fabricated using common semiconductor device manufacturing processes. For example, the laser devices may be made from common semiconductor wafer substrates that have epitaxial waveguide layers grown on them. The lasing and the beam-deflecting sections of the laser devices may be made from adjacent cleaved substrate pieces. The two sections may be assembled in close proximity by rejoining cleaved wafer pieces along the cleavage facets. Alternatively, the lasing and the beam-deflecting sections may be formed from adjacent uncleaved substrate pieces, but which are delimited by narrow trenches etched through the epitaxial layers.

Further, for example, common wet etching techniques using anisotropic etchants may be used to form the deflection surface which is used for total internal reflection of light. Suitable anisotropic etchants such as HBr solutions may be used to form V-groove shaped etch pits, the sides of which are crystallographically terminating etch planes. A suitably oriented side may be used as the deflecting surface.

Further, common semiconductor processing materials such as photo-resists, oxides or nitrides may be used to form the micro-optic lens disposed on the top surface of the device. For example, the micro-optic lens may be formed by resist reflow. The parameters of the resist reflow processes may be suitably adjusted to obtain lenses with a focal length suitable for collimating the output light beam.

5 structures minimizes the need for external beam-shaping
or focusing optics.

Brief Description of the Drawings

10 following detailed description, taken in conjunction
with the accompanying drawings, in which like reference
characters refer to like parts throughout, and in
which:

FIG. 1 is a cross-sectional view of a conventional vertical cavity surface-emitting laser device structure;

FIG. 2 is a cross-sectional view of a conventional grating-coupled surface-emitting laser device structure;

FIG. 3 is a cross-sectional view of a conventional surface-emitting laser device structure with an integrated 45-degree mirror as part of the lasing cavity;

FIG. 4 is a cross-sectional view of a
25 conventional surface-emitting laser device structure
with an integrated 45-degree mirror external to the
lasing cavity;

FIG. 5a is a cross-sectional view of a surface-emitting laser device structure in accordance with the principles of this invention;

FIG. 5b is a cross-sectional view of another surface-emitting laser device structure in accordance with the principles of this invention;

FIG. 5c is a plan view of the

FIG. 6a is a cross sectional view of a

FIG. 6b is a plan view of the

10

The present invention is described herein in

However, references to the InP material

The inventive surface-emitting laser device

placed in close proximity. The adjacent pieces from which the two sections are made may be cleaved apart to form laser cavity facets, and then mechanically rejoined. Unlike dicing, cleaving semiconductors along
5 crystal planes does not generate material loss.

Adjacent cleaved pieces may be rejoined with a gap of less than about a thousand angstroms between them. Known techniques for cleaving and rejoining semiconductor facets such as wafer bonding may be used.
10 Using such techniques, it also may be possible to use non-adjacent cleaved pieces of the substrate for making the two sections. If for example, the cleaved facets of the non-adjacent pieces have suitable mutually conforming shapes, they may be satisfactorily rejoined.

15 Alternatively, the lasing section and the beam-deflecting section may be delimited by etching a vertical trench between the adjacent pieces from which the two sections are made. The vertical trench may extend through the epitaxial waveguide layers on the
20 substrate. A trench sidewall may provide an etched facet for one end of the lasing section.

The close proximity of the two sections in the device ensures efficient transmission of emitted light from the lasing section to the beam-deflecting
25 section. Light transmission or coupling efficiencies of about 85% may be expected. At the same time, the distinct separation of the two sections by cleaved or etched facets minimizes any adverse effect of the close proximity of the second section on the lasing action of
30 the first section. The output power, threshold current, frequency response, and other lasing characteristics of the laser device may be determined

05071229 052404

primarily by the first section (i.e., lasing section) of the device structure.

FIGS. 5a, 5b, and 5c illustrate two structural embodiments of a surface-emitting laser 5 in accordance with the present invention. Laser 5 includes an edge-emitting lasing section 50 and a beam-deflecting section 51. Both sections 50 and 51 include an active waveguide layer 52 bounded by upper and lower cladding layers 52a, and a bottom reflector/electrode 54. Top electrode 53 may extend over lasing section 50, and may also extend over section 51 as shown in the FIGS 5a, 5b and 5c. Electrodes 53 and 54 are connected to suitable laser driver circuits (not shown). Beam-deflecting section 51 further includes a light deflecting surface 57 and a micro-optic lens 56.

Laser 5 may be fabricated on InP substrate 500 using conventional semiconductor processing techniques, for example, to grow epitaxial layers and deposit metal electrode layers. The same epitaxial materials that are traditionally used in conventional InP-based EELs may be used. Cladding layers 52a may, for example, be formed using p- and -doped InP. Active waveguide layer 52 may, for example, be made of a series of one or more AlInGaAs or InGaAsP quantum wells or be made of a bulk InP layer about 2000 Å thick. To improve laser performance, a graded index region may be formed on either side of active layer 52 to enhance the optical confinement (not shown). A low-bandgap compound semiconductor (e.g., InGaAs) layer (not shown) may also be formed on the top of the epitaxial cladding layers to facilitate ohmic contact by metal electrode 53.

5

20

25

30

Any suitable processing technique may be used to form trench 55a. For example, conventional dry etching processes such as reactive ion etching (RIE), chemical assisted ion beam etching (CAIBE), electron cyclotron resonance etching (ECR), and inductive coupled plasma etching (ICP) may be used for etching trench 55a. The close proximity of sections 50 and 51 necessary for efficient optical coupling may require that trench 55a be narrow. The narrowness of trench 55a may lead to masking effects and other deleterious process effects during etching. The masking effects and the other deleterious process effects may result in damage to etched facets 55b. However, with sufficient care during processing, damage to etched facets 55b may be avoided. Also, continuing advances in ECR, ICP, and other dry etching techniques and chemistries show promising process capability for routinely etching narrow trenches with high-quality facets. For example, trenches as narrow as 1 μm across between sections 50 and 51 have been etched (in InP) by ICP using HBr-based gases as the etching gases instead of the more commonly used CH_4/H_2 gases.

For the embodiments of laser 5 shown in FIGS. 5a and 5b, either respective cleaved facet 55 or respective etched facet 55b defines one end of a lasing cavity formed by active portion 52 in lasing section 50. In operation, light emission in laser 5 occurs perpendicular to facet 55 (or facet 55b), and propagates horizontally toward deflecting surface 57 (i.e., toward the right in FIGS. 5a and 5b).

Deflecting surface 57 may be formed by a crystallographically terminating etch plane. Surface 57 may be formed using any suitable dry etching

techniques such as RIE, ECR, ICP, CAIBE, and ion milling. Surface 57 also may be formed by wet chemical etching using, for example, hydrogen bromide (HBr) solution as an etchant. Anisotropic etchants such as

5 HBr solutions may be suitable for making self-limiting V-groove shaped etch pits. The sides of the V-groove shaped etch pits are crystallographically terminating etch planes. One side of a sufficiently large V-groove shaped etch pit may serve as deflecting surface 57.

10 The terminating etch plane may be a suitable crystallographic plane chosen to exploit the phenomenon of total internal reflection. The crystallographic plane is chosen such that the angle it forms with a horizontal plane (parallel to the top surface) through

15 active portion 52 exceeds the critical angle for total internal reflection. Because active portion 52 has a finite cross-sectional area and light radiation emitted from facet 55 is divergent, not all of the emitted light is incident on surface 57 at the same angle.

20 However, because of the close proximity of the lasing section 50 and surface 57, most, if not all, of the emitted light is likely to be incident at angles greater than the critical angle. Therefore, most of the emitted light incident on surface 57 is likely to

25 undergo total internal reflection, and to be directed through transparent substrate 500 toward bottom reflector 54 (e.g., beam 58d). Reflection efficiencies as high as 80% may be obtained with a suitably formed surface 57.

30 Bottom reflector 54 redirects the light incident on it in a generally upward direction (e.g., beam 58u) toward the top wafer surface on which micro-optic lens 56 is disposed. Bottom reflector 54

05871229 "053104
TOP SECRET

perpendicular to the surface of the wafer and is vertically aligned over the intersection of active area 52 and deflecting surface 57. In lateral or horizontal extent lens 56 is primarily disposed over beam-deflecting section 51, but also may extend sufficiently over lasing section 51 to capture all of the vertically emerging light beam spot (e.g., spot 58e FIG. 5c).

Micro-optic lens 56 may be formed at the same time as structures 59 (FIG. 5c) that hold sections 50 and 51 together are formed. For example, reflowed resist may be used to make both micro-optic lens 56 and structure 59. A resist-reflowed lens uses refractive phenomena to collimate light, and may have a generally hemispherical shape. Lens focal length is determined by the radius of curvature of the hemispherical shape. The radius of curvature of the hemispherical shape may be adjusted by controlling resist reflow parameters to obtain a desired lens focal length. The shape may also be suitably modified to reduce aberration and to achieve a more circular cross-section for output beam 58. Using resist-reflowed lenses, lens-to-optical fiber coupling efficiencies of about 20% and 60% may be achieved for single-mode fibers and multi-mode fibers, respectively.

Alternatively, lens 56 may utilize diffraction phenomena to collimate light. Diffraction lenses (e.g., Fresnel lenses) may be made, for example, by disposing suitable diffraction gratings on the top surface of the laser structure (not shown). The diffraction grating may be made, for example, by dry etching, or by deposition of material such as oxides or nitrides.

09874329 0524

The capability of the inventive laser device structures to include an integrated beam-shaping lens is a direct consequence of the long optical path length of twice-reflected emitted light in section 51

5 (reflected first off surface 57 and then off bottom reflector 54). The optical path length without the total internal reflection off surface 57 and reflection off bottom reflector 54 (as in prior art beam-deflecting mirror SELS) would be considerably
10 shorter. Micro-optic lenses with short focal lengths have correspondingly small radii of curvature. Such lenses are both difficult to make and to integrate into laser device structures.

The overall efficiency of coupling light
15 emission from lasing section 50 to optical fibers (i.e., the percent of section 50 output power that is injected into an optical fiber) depends on designable characteristics of individual elements of the inventive laser device structures. For example, the overall
20 efficiency depends on the efficiency of light coupling between section 50 and 51, the reflective efficiencies of surface 57 and bottom reflector 54, and the coupling efficiency of lens 56. These individual element characteristics may be optimized by design of each
25 individual element. For example, reflective efficiency of bottom reflector 54 may be increased by using high reflectivity multi-layer coatings instead of using a single aluminum metal coating mentioned earlier.

Still, using the numbers for the efficiency
30 of light coupling between section 50 and 51 (85%), the reflective efficiencies of surface 57 and bottom mirror 54 (80% and 90%, respectively), and the coupling efficiency of lens 56 (20% for single-mode fibers, and

09071229-052404

In addition to external beam-shaping or focusing optics, traditional laser modules also often use separate power-monitoring detectors for monitoring laser output and to provide feedback to stabilize laser output (e.g., back facet power-monitoring detectors used with conventional EELs). Conventional separate power-monitoring detectors that are suitable for 1.3 μm and 1.55 μm wavelengths are expensive InGaAs or Ge photodetectors. As explained below following a discussion of the typical dimensions of sections 50 and 51, the inventive laser device structures may include integrated power-monitoring detectors. Integrating power-monitoring detectors with the laser device structures obviates the need for, and the costs associated with, separate power-monitoring detectors that are used with traditional laser modules.

Lasing section 50 and the beam-deflecting section 51 may each be about a few hundred microns long. The two sections may have unequal lengths. 30 Lasing section 50 may, for example, be 300 μm long, while beam-deflecting section 51 may, for example, be 150 μm long. The length of lasing section 50 is primarily determined by the designed length of the

Portions of beam-deflecting section 51 not used for beam deflection may optionally be used for an integrated power-monitoring detector. This power-monitoring detector may be used to monitor the laser output power and to provide feedback to laser driver circuits for stabilizing laser output.

30 In the operation of laser 6, emitted light generated by lasing section 51 propagates horizontally toward deflecting surface 57. The horizontally propagating light, as described above (FIGS. 5a 5b, and

5c), is mostly redirected towards bottom reflector 54 by deflecting surface 57. However, a small fraction of the emitted light is absorbed in active portion 52 of beam-deflecting section 51 while propagating toward
5 deflecting surface 57. The amount of light absorbed is determined by factors such as the optical confinement factor and the length (in section 51) of active portion 52 preceding surface 57. This light absorption in active portion 52 generates photo-excited carriers.
10 Since top electrode 53 does not extend over section 51, active portion 52 (in section 51) is not electrically pumped (i.e., is not itself lasing). Therefore, active portion 52 can function as a power-monitoring detector. The number of photo-excited carriers generated in
15 active portion 52 is proportional to the laser power output. The generated photo-excited carriers are collected by electrode 61 producing a photocurrent proportional to laser output.

The processes for making individual elements
20 of different embodiments of inventive laser device have been generally described above. The elements and the processes for making them were described in a particular sequence in the context of explaining the operation of the laser device. With this perspective
25 view, it will be understood that this particular sequence may not necessarily be the sequence of process steps used in the fabrication of the laser devices. An illustrative sequence of process steps that may be used in the fabrication of the laser devices may, for
30 example, be as follows:

prepare an epitaxial multiple-layer structure including, for example, upper and lower cladding layers and an active layer, on a semiconductor

00074220 053404

form lasing waveguides with top metal
electrode contacts using conventional processes for
5 making edge-emitting lasers;

```

10  thin the substrate by back lapping the
    substrate;

```

```

define lasing and beam-deflection
15 sections of laser devices by cleaving adjacent
   substrate pieces or by etching delimiting trenches
   between adjacent substrate pieces;

```

form beam-shaping micro-optic lenses on top surfaces of the lasing sections and the beam-deflection sections; and

The sequence of process steps listed above is only illustrative and may be performed in any suitable order. In practice, some of the steps may be omitted, and additional steps that are not listed above may be included in the fabrication of the inventive laser devices.

It will be understood that the foregoing is only illustrative of the principles of the invention, and that various modifications can be made by those skilled in the art without departing from the scope and
5 spirit of the invention.

09071229 053107